CleanAIR® by maxisafe. Omnira COMBI ONE SOLUTION FOR MANY NEEDS DUE **APRIL** 2022



ONE SOLUTION FOR MANY NEEDS

Autodarkening welding helmet with an advanced built-in air distribution system and flip-up welding shield. Provides protection of the user's eye and face from harmful radiation including visible light, ultra-violet(UV), infra-red (IR) radiation, hot sparks and spatters resulting from arc welding and cutting. At the same time it provides protection against high speed particles. It is adapted for use with powered air purifying respirators CleanAIR® or with continuous flow compressed air breathing apparatuses CleanAIR®.

Professional flip-up welding helmet suitable for most of welding processes such as MIG/MAG, SMAW, TIG, Plasma Arc welding and cutting, Carbon Arc gouging, gas welding and cutting. Thanks to the large clear visor it is very convenient for grinding.

- The highest respiratory protection and more comfort thanks to an advanced built-in air distribution system
- True colour ADF with the highest optical quality 1/1/1/1
- Fast and easy replacement of all spare parts

Expand your perspective

LIFT UP

The flip-up front can be lifted up whenever the wide undisturbed view is needed.



STAY PROTECTED

The flip-up system allows you to switch between welding and grinding without compromising respiratory protection.



BE VERSATILE

For extended non-welding jobs, simply remove the welding visor completely with one click.



Multiple protection – eye, face and respiratory at once

NATURAL COLORS

True colour ADF with the highest optical quality 1/1/1/1.

FAST CHANGE

Fast and easy replacement of protective plates.

GRIND MODE CONTRO

Easily accessible from the outside of the helmet.

LIFT LIP

The flip-up front can be lifted up whenever the wide undisturbed view is needed.

CLICK-IN SYSTEM

The flip-up front can be easily removed and attached back thanks to unique

VISOR OPTIONS

Clear visor of the highest optical quality can be easily changed for avaliable alternative visors (yellow; shade 3,5; cylindrical with protection films).

Lightweight and durable shell,

of EN 175 B and thus ensuring protection against high speed

particles.

meets the requirements

ANGLE CONTROL

The tilt adjustment knob is easily accessible from the outside of the helmet.

FULLY ADJUSTABLE

Outer control of the direction of the air

Compatible powered air purifying respirators / airline systems

AerGO®





Chemical 2F



Pressure Flow Master



Pressure



VariGEAR

CleanAIR®

FITS ALL HEAD SHAPES

Newly designed head suspension allows multiple individual settings.

SOFT PADDINGS

The soft padding sits gently on the top of the head and ensures better weight distribution and a perfect fit.

ie ver

The crown part of the headgear is vertically adjustable to fit all head shapes and sizes.

OUICK REPLACEMENT

Easy replacement of the headgear just by sliding it out of the holder.

CUSTOMISABLE

Easy adjustment of the distance between the face of the welder and the visor.
Keep the visor as close as possible to your eyes for a wider view and minimum neck strain.

HOSE HOLDER

Easily removable hose holder can be placed either


COMEDET END VOLID HEAT

The soft padding of the back part of the headgear swivels to fit different head shapes.

PRECISE FIT

The smooth ratchet mechanism allows precise adjustment of the head circumference

Adjustable air flow



For more individual comfort you can regulate the airflow in two zones

Zone 1 – Control knob accessible from outside the helmet controls the direction of the air coming from the lower part of the airduct.

Zone 2 – The two other outputs are located in the upper part of the helmet. The intensity of the airstream can be regulated by the two sliders inside the helmet.

Superb optics for your better view - ADF S60F



TRUE COLOUR TECHNOLOGY

True colour display
for increased colour
perception
and excellent clarity
of vision at all time

Large viewing area 98 x 62 mm

- Superb optics for a better view
- Ten available dark shades for various welding jobs
- The delay function allows the user to set the switching time from dark to light
- A wide range of sensitivity settings allow the welder to adapt the ADF to all welding processes
- Four sensors for stable arc detection
- Smart power control auto ON, auto OFF (after 30 min if not in use)
- Meeting the highest requirements according to EN 379 for eye protection of welders

Extend your protection

available accessories*

Protective head cover, flame retardant 70 30 71 Protective neck cover, flame retardant 70 30 72

* comes standard with CleanAIR® Omnira COMBI air





Omnira COMBI air

by maxisafe.

Helmet technical specifications

Weight	1017 g
Material	Welding shield - PA ADF - PA, PC, Glass Protection plate - PC Headgear - PP, PA
Hose connection	 QuickLOCK™
Certification / NPF – respiratrory protection	powered air purifying respirators - EN 12941, TH3 / NPF 500
	airline sytems (supplied air) - EN 14594 (3B) / NPF 200
Certification – eye and face protection	protective visor TR1 - EN166 1 FT B K N
	frame - EN166 3 4 5 FT B 5/2-5

ADF technical specifications

ADF dimensions	110 x 90 x 7 mm
Viewing area	98 x 62 mm
Shade range	dark state, variable 5-8 / 9-14
	light state 3
Switching time	0,00015 s (0,15 ms) - light to dark
	0,1 - 0,9 s (adjustable) - dark to light

Product name	Product code
Omnira Flip-up Welding Helmet incl. ADF S60+ Shade 5-14	RW01127
Omnira Flip-up Welding Helmet incl. ADF S60+ Shade 5-14, combined with Basic PAPR Belt Unit	RW01127-CB
Omnira Flip-up Welding Helmet incl. ADF S60+ Shade 5-14, combined with AerGO PAPR Belt Unit	RW01127-CA
Omnira Flip-up Welding Helmet incl. ADF S60+ Shade 5-14, combined with Pressure PAPR Belt Unit	RW01127-CP



Techware Pty Ltd 30 Bonview Circuit, Truganina Victoria, Australia 3029
Tel.: 1300 062 947 | sales@techware.net.au