

CleanAIR® Mask Mount Asbest PAPR with Full Face Mask

CleanAIR®



Features & Benefits

- Exceptionally light and compact combination ideal for asbestos handling
- High nominal protection factor (NPF 2000)
- Simple operation and decontamination by shower
- Lithium-Ion 7.2 V, 2.2 Ah exchangeable battery
- Operation time up to 5 hours with low battery indicator
- Superior, spherical visor eliminates distortion and offers broad view
- Anti-scratch visor also with replaceable protection cover
- 6-point harness with non-sticky surface prevents hair entanglement

Applications

- Asbestos Handling
- Sanding or Grinding
- Construction Industry
- Cleaning

Product Code

RPA531a

CF02 Mask Specifications

Weight: 435 g (both sizes)
Material: Mask Body – thermoplastic elastomer TPE visor – polycarbonate
Head Harness – polybutylene terephthalate TPU

Protection Factor: (NPF) 2000

Asbest Nose-Mount PAPR Specifications

Weight: 385 g (including battery and filter)
Airflow: 180 lpm
Filter Type: Particle P R SL
Battery: Li-Ion 7,2V / 2.8 Ah
Operation* / charging time: 3/5 h

 [CLICK HERE FOR PRODUCT SPEC](#)

there's safe and there's Maxisafe.